

HEM Horizontal Pivot: H130HA-CTS

Capacity: 18" W x 14" H, 19" W x 10" H (Rectangle), 16" W x 16" H (Square) • Blade: 1-1/2" x 17'0" x .050"
Motor: 10 HP • Hydraulics: 2 HP • Bar-feed: 0-24" Stroke Hydraulic Cylinder (Multiple Index)



Standard Features

- Swing-Away Control Console w/ Touch Screen
- Computer Controlled Feed System
- 24" Solid Discharge Table – Bolts to Saw
- Full Stroking Vises w/ Adjustable Clamping Force
- Adjustable Blade Speed w/ Readout on Touch Screen
- Powered Guide Arm
- Carbide Blade Guides
- Roller Guides – Entry & Exit
- Cut Watcher® System
- Adjustable Cutting Force & Feed Rate
- Powered Blade Tension
- Chip Auger System
- Material Jogging
- Vertical Alignment Roller on Feed
- Flood Coolant System w/ Wash-Down Hose
- Broken Blade & Out of Stock Indicators
- Safety Guards
- 220V/440V/3PH Electrical Motor Requirement
- This is Not a Dual Voltage Machine



Optional Features

- 0-48" Stroke Servo Twin Ball-Screw Bar-Feed
- Full Capacity Top Clamp – Main & Feed Vise
- Reduced Capacity Top Clamp – Feed Vise
- Reduced Capacity Top Clamp – Main Vise
- Outboard Powered Vise on Discharge
- 3rd Holding Vise on Feed
- Interlocking Vise Jaws
- Laser Light System
- Spray Mist Lubrication
- Optional Control Consoles
- 5' or 10' Idle Roller Stock Table

HEM[®] SAW
— The saw that cuts straight. —

www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74362 • Toll Free: 888-729-7787 • Email: info@hemsaw.com

HE&M, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HE&M, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HE&M, Inc. All rights reserved.

HEM Horizontal Pivot: H130HM-1

Capacity: 18" W x 14" H, 19" W x 10" H (Rectangle), 16" W x 16" H (Square) • Blade: 1-1/2" x 17'0" x .050"
Motor: 10 HP • Hydraulics: 2 HP



Standard Features

- Swing-Away Console – Manual Control
- 24" Solid Discharge Table – Bolts to Saw
- Full Stroking Main Vise
- Adjustable Clamping Force
- Push Button Blade Speed w/ LED Readout
- Carbide Blade Guides
- Roller Guides – Entry & Exit
- Powered Guide Arm
- Adjustable Cutting Force & Feed Rate
- Powered Blade Tension
- Blade Brush
- Flood Coolant System w/ Wash-Down Hose
- Broken Blade Indicator
- Safety Lockout Key & Safety Guards

220V/440V/3PH Electrical Motor Requirement
– This is Not a Dual Voltage Machine

Optional Features

- Full Capacity Top Clamp – Main Vise
- Reduced Capacity Top Clamp – Main Vise
- Outboard Powered Vise on Discharge
- Chip Auger System
- Cut Watcher® System
- Laser Light System
- Spray Mist Lubrication
- Pedestal Mounted Console
- 10' Roller Load Table
- 5' or 10' Idle Roller Stock Table

HEM[®] SAW
— The saw that cuts straight. —

www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74362 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HE&M, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HE&M, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HE&M, Inc. All rights reserved.