



TruTool TKA 700

Technical data

TruTool TKA 700 without tool

TruTool TKA 700 45° tool

MAXIMUM CHAMFER LENGTHS / MAXIMUM CHAMFER HEIGHTS

Maximum chamfer length, steel 400 N/mm ²	7 mm	7 mm
Maximum chamfer height, steel 400 N/mm ²	4.9 mm	4.9 mm
Maximum chamfer length, steel 600 N/mm ²	3.7 mm	3.7 mm
Maximum chamfer height, steel 600 N/mm ²	2.5 mm	2.5 mm
Maximum chamfer length, steel 800 N/mm ²	2.3 mm	2.3 mm
Maximum chamfer height, steel 800 N/mm ²	1.6 mm	1.6 mm
Maximum chamfer length, aluminium 250 N/mm ²	10 mm	10 mm
Maximum chamfer height, aluminium 250 N/mm ²	6.4 mm	6.4 mm

RADII

Smallest inner radius	18 mm	18 mm
Smallest bore hole (Ø)	35 mm	35 mm

GENERAL

Minimum sheet thickness	1.5 mm + hs	1.5 mm + hs
Working speed (max.)	4 m/min	4 m/min
Nominal power consumption	1700 W	1700 W

DIMENSIONS

Length	365 mm	365 mm
Height	152 mm	152 mm

WEIGHT

Weight	3.9 kg	3.9 kg
--------	--------	--------