

Standard Industrial Company

1115 Hwy. 49 South / Desoto Street

Clarksdale, MS. 38614

Phone: 662.624.2436 • Fax: 662.624.2581

Email: vance@standard-industrial.com • Website: www.standard-industrial.com**Press Brakes AB Series [250 to 325 to 400 Tonnage Presses]****Our brakes were specifically designed for the following applications**

- Full length bends where full tonnage across the bed is a necessity for the truest bends
- Off-center loading when any amount of the brakes tonnage is needed across the bed
- Center loading where any amount of the brakes tonnage is required
- Multiple die set-ups across the bed that require varying amounts of tonnage
- Punching applications in one area or at varied locations across the bed - each brake has a counter balance valve to allow the least shock to the hydraulic system
- Short piece work, with some of the fastest ram speeds on any brake, your small piece work is done quickly, easily and with precision.
- Any Size Facility will benefit for the Standard Industrial brake from the price conscious smaller facility that does piece by piece work up to the 3 shifts a day high production manufacturers that require dependable, low maintenance machines with readily available components for minimal downtime

Results 1 - 12 of 12

<u>Model</u>	<u>Shipping Weight</u>	<u>Forming / Punching</u>	<u>Bed/Ram Length</u>	<u>Between Frames</u>	<u>Open Height</u>	<u>Stroke</u>
AB250-12	40,000 lbs	250 / 165 Tons	12 ft	10'-5"	16 in	8 in
AB250-14	50,000 lbs	250 / 165 Tons	14 ft	12'-5"	16 in	8 in
AB250-16	56,000 lbs	250 / 165 Tons	16 ft	14'-5"	16 in	8 in
AB250-20	85,000 lbs	250 / 165 Tons	20 ft	16'-5"	16 in	8 in
AB325-12	49,000 lbs	325 / 215 Tons	12 ft	10'-5"	16 in	8 in
AB325-14	60,000 lbs	325 / 215 Tons	14 ft	12'-5"	16 in	8 in
AB325-16	66,000 lbs	325 / 215 Tons	16 ft	14'-5"	16 in	8 in
AB325-20	100,000 lbs	325 / 215 Tons	20 ft	16'-5"	16 in	8 in
AB400-12	58,000 lbs	400 / 265 Tons	12 ft	10'-5"	20 in	10 in
AB400-14	67,000 lbs	400 / 265 Tons	14 ft	12'-5"	20 in	10 in
AB400-16	80,000 lbs	400 / 265 Tons	16 ft	14'-5"	20 in	10 in
AB400-20	110,000 lbs	400 / 265 Tons	20 ft	16'-5"	20 in	10 in

Results 1 - 12 of 12