

## Press Brakes AB Series [100 to 150 to 200 Tonnage Presses]



### Our brakes were specifically designed for the following applications

- Full length bends where full tonnage across the bed is a necessity for the truest bends
  - Off-center loading when any amount of the brakes tonnage is needed across the bed
  - Center loading where any amount of the brakes tonnage is required
  - Multiple die set-ups across the bed that require varying amounts of tonnage
  - Punching applications in one area or at varied locations across the bed - each brake has a counter balance valve to allow the least shock to the hydraulic system
  - Short piece work, with some of the fastest ram speeds on any brake, your small piece work is done quickly, easily and with precision.
- Any Size Facility will benefit for the Standard Industrial brake from the price conscious smaller facility that does piece by piece work up to the 3 shifts a day high production manufacturers that require dependable, low maintenance machines with readily available components for minimal downtime

Results 1 - 17 of 17

<u>Model</u>	<u>Shipping Weight</u>	<u>Forming / Punching</u>	<u>Bed/Ram Length</u>	<u>Between Frames</u>	<u>Open Height</u>	<u>Stroke</u>
<a href="#">AB100-6</a>	12,000 lbs	100 / 66 Tons	6 ft	4'-5"	13 in	6 in
<a href="#">AB100-8</a>	15,000 lbs	100 / 66 Tons	8 ft	6'-5"	13 in	6 in
<a href="#">AB100-10</a>	19,000 lbs	100 / 66 Tons	10 ft	8'-5"	13 in	6 in
<a href="#">AB100-12</a>	21,000 lbs	100 / 66 Tons	12 ft	10'-5"	13 in	6 in
<a href="#">AB100-14</a>	26,000 lbs	100 / 66 Tons	14 ft	12'-5"	13 in	6 in
<a href="#">AB100-16</a>	32,000 lbs	100 / 66 Tons	16 ft	14'-5"	13 in	6 in
<a href="#">AB100-20</a>	50,000 lbs	100 / 66 Tons	20 ft	18'-5"	13 in	6 in
<a href="#">AB150-8</a>	19,000 lbs	150 / 100 Tons	8 ft	6'-5"	13 in	6 in
<a href="#">AB150-10</a>	22,000 lbs	150 / 100 Tons	10 ft	8'-5"	13 in	6 in
<a href="#">AB150-12</a>	26,000 lbs	150 / 100 Tons	12 ft	10'-5"	13 in	6 in
<a href="#">AB150-14</a>	31,000 lbs	150 / 100 Tons	14 ft	12'-5"	13 in	6 in
<a href="#">AB150-16</a>	38,000 lbs	150 / 100 Tons	16 ft	14'-5"	13 in	6 in
<a href="#">AB150-20</a>	72,000 lbs	150 / 100 Tons	20 ft	18'-5"	13 in	6 in
<a href="#">AB200-12</a>	32,000 lbs	200 / 135 Tons	12 ft	10'-5"	14 in	8 in
<a href="#">AB200-14</a>	45,000 lbs	200 / 135 Tons	14 ft	12'-5"	14 in	8 in
<a href="#">AB200-16</a>	50,000 lbs	200 / 135 Tons	16 ft	14'-5"	14 in	8 in
<a href="#">AB200-20</a>	85,000 lbs	200 / 135 Tons	20 ft	18'-5"	14 in	8 in

Results 1 - 17 of 17

Press Brakes AB Series [250 to 325 to 400 Tonnage Presses]



**Our brakes were specifically designed for the following applications**

- Full length bends where full tonnage across the bed is a necessity for the truest bends
- Off-center loading when any amount of the brakes tonnage is needed across the bed
- Center loading where any amount of the brakes tonnage is required
- Multiple die set-ups across the bed that require varying amounts of tonnage
- Punching applications in one area or at varied locations across the bed - each brake has a counter balance valve to allow the least shock to the hydraulic system
- Short piece work, with some of the fastest ram speeds on any brake, your small piece work is done quickly, easily and with precision.
- Any Size Facility will benefit for the Standard Industrial brake from the price conscious smaller facility that does piece by piece work up to the 3 shifts a day high production manufacturers that require dependable, low maintenance machines with readily available components for minimal downtime

Results 1 - 12 of 12

<u>Model</u>	<u>Shipping Weight</u>	<u>Forming / Punching</u>	<u>Bed/Ram Length</u>	<u>Between Frames</u>	<u>Open Height</u>	<u>Stroke</u>
<a href="#">AB250-12</a>	40,000 lbs	250 / 165 Tons	12 ft	10'-5"	16 in	8 in
<a href="#">AB250-14</a>	50,000 lbs	250 / 165 Tons	14 ft	12'-5"	16 in	8 in
<a href="#">AB250-16</a>	56,000 lbs	250 / 165 Tons	16 ft	14'-5"	16 in	8 in
<a href="#">AB250-20</a>	85,000 lbs	250 / 165 Tons	20 ft	16'-5"	16 in	8 in
<a href="#">AB325-12</a>	49,000 lbs	325 / 215 Tons	12 ft	10'-5"	16 in	8 in
<a href="#">AB325-14</a>	60,000 lbs	325 / 215 Tons	14 ft	12'-5"	16 in	8 in
<a href="#">AB325-16</a>	66,000 lbs	325 / 215 Tons	16 ft	14'-5"	16 in	8 in
<a href="#">AB325-20</a>	100,000 lbs	325 / 215 Tons	20 ft	16'-5"	16 in	8 in
<a href="#">AB400-12</a>	58,000 lbs	400 / 265 Tons	12 ft	10'-5"	20 in	10 in
<a href="#">AB400-14</a>	67,000 lbs	400 / 265 Tons	14 ft	12'-5"	20 in	10 in
<a href="#">AB400-16</a>	80,000 lbs	400 / 265 Tons	16 ft	14'-5"	20 in	10 in
<a href="#">AB400-20</a>	110,000 lbs	400 / 265 Tons	20 ft	16'-5"	20 in	10 in

Results 1 - 12 of 12

Press Brakes AB Series [500 to 600 to 700 to 1,000 Tonnage Presses]



**Our brakes were specifically designed for the following applications**

- Full length bends where full tonnage across the bed is a necessity for the truest bends
- Off-center loading when any amount of the brakes tonnage is needed across the bed
- Center loading where any amount of the brakes tonnage is required
- Multiple die set-ups across the bed that require varying amounts of tonnage
- Punching applications in one area or at varied locations across the bed - each brake has a counter balance valve to allow the least shock to the hydraulic system
- Short piece work, with some of the fastest ram speeds on any brake, your small piece work is done quickly, easily and with precision.
- Any Size Facility will benefit for the Standard Industrial brake from the price conscious smaller facility that does piece by piece work up to the 3 shifts a day high production manufacturers that require dependable, low maintenance machines with readily available components for minimal downtime

Results 1 - 14 of 14

<u>Model</u>	<u>Shipping Weight</u>	<u>Forming / Punching</u>	<u>Bed/Ram Length</u>	<u>Between Frames</u>	<u>Open Height</u>	<u>Stroke</u>
<a href="#">AB500-12</a>	70,000 lbs	500 / 300 Tons	12 ft	10'-5"	20 in	10 in
<a href="#">AB500-14</a>	80,000 lbs	500 / 300 Tons	14 ft	12'-5"	20 in	10 in
<a href="#">AB500-16</a>	87,000 lbs	500 / 300 Tons	16 ft	14'-5'	20 in	10 in
<a href="#">AB500-20</a>	129,000 lbs	500 / 300 Tons	20 ft	16'-5"	20 in	10 in
<a href="#">AB600-12</a>	87,000 lbs	600 / 400 Tons	12 ft	10'-5"	22 in	10 in
<a href="#">AB600-14</a>	97,000 lbs	600 / 400 Tons	14 ft	12'-5"	22 in	10 in
<a href="#">AB600-16</a>	108,000 lbs	600 / 400 Tons	16 ft	14'-5"	22 in	10 in
<a href="#">AB600-20</a>	150,000 lbs	600 / 400 Tons	20 ft	16'-5"	22 in	10 in
<a href="#">AB700-14</a>	112,000 lbs	700 / 465 Tons	14 ft	12'-5"	24 in	12 in
<a href="#">AB700-16</a>	135,000 lbs	700 / 465 Tons	16 ft	14'-5"	24 in	12 in
<a href="#">AB700-20</a>	180,000 lbs	700 / 465 Tons	20 ft	16'-5"	24 in	12 in
<a href="#">AB1000-14</a>	160,000 lbs	1000 / 600 Tons	14 ft	12'-5"	24 in	12 in
<a href="#">AB1000-16</a>	170,000 lbs	1000 / 600 Tons	16 ft	14'-5"	24 in	12 in
<a href="#">AB1000-20</a>	195,000 lbs	1000 / 600 Tons	20 ft	16'-5"	24 in	12 in

Results 1 - 14 of 14